NSN 5935-01-264-0240

Electrical Receptacle Connector Body - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-264-0240 |
|--|
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.044 inches |
| Overall Height: |
| 1.312 inches |
| Overall Width: |
| 1.312 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.123 inches and 0.138 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.062 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.062 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.627 inches and 0.632 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 16-35 single mating end |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 330.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416 federal specification single treatment response |
| Special Features: |
| 17-35 insert configuration |
| Test Data Document: |
| 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 96906-ms27496 government standard |

N/a

Shelf Life:

NSN 5935-01-264-0240

Electrical Receptacle Connector Body - Page 2 of 2



| Demilitarization: | |
|-------------------|--|
| No | |
| Fiig: | |
| A039b0 | |

Mil-std (military Standard):

Mil-c-38999 spec.

Unit Of Measure: