Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-264-0669

Thread Oraciton: Right-hand Seal Material: Rubber, neoprene latex Overall Height: 3.875 Inches Overall Height: 3.875 Inches Overall Height: 3.883 Inches Overall Height: 1.888 Inches Overall Widht: 1.375 Inches Cable Opening Dameter: 0.750 Inches Cable Opening Quantity: 1 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 Inches Matrial: Auminum alloy Surface Treatment: Cadmium Stright type wickele clamp Surface Treatment: Cadmium Thread Size: Stright type wickele clamp Surface Treatment: Cadmium Thread Size Cadmium Thread Size Cadmium Surface Treatment: Cadmi		
Righ-hand Sad Matrial: Righ-hand Sad Matrial: Righ-hand Subbar, neapyone latex: Overall Height: 3.875 inches Overall Height: 1.888 inches Overall Widht: 1.375 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 1 Seat Type: Preformed packing Mounting Facility Type And Quantity: 1 Thread Step 1.125 inches Steriation Striated coupling Thread Step 1.125 inches Striated Coupling Striated Coupling Striated Coupling Thread Step 1.125 inches Striated Coupling Striated Coupling Striated Treatment: Cadmium Striate Treatment: Cadmium Striate Treatment: Cadmium Striate Treatment: Cadmium	Thread Class:	
Right-hand Seal Material: Rubber, neoprene latex Overall Length: 3.875 Inches Overall Height: 1.888 Inches Overall Midth: 1.888 Inches Overall Midth: 1.375 Inches Cable Opening Diameter: 0.750 Inches Cable Opening Diameter: 0.750 Inches Cable Opening Quantity: 1 1 Seal Type: Preformed packing Mounting Facility type And Quantity: 1 threaded Duping Thread State: 1.125 Inches Material: 1.25 Inches Material: Auterial: Auterial: Auterial: Auterial: State Teatment: Cadmium State Teatentent: I	2b	
Sea Material: Rubber, neoprene tatex Overall Length: 3.875 inches Overall Height: 1.888 inches Overall Width: 1.375 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Performed packing Mounting Facility Type And Quantity: 1 Performed packing Mounting Facility Type And Quantity: 1 1: Seal Type: Performed packing Mounting Facility Type And Quantity: 1:	Thread Direction:	
Rubber, neoprene latex Overall Length: 3.876 inches Overall Width: 1.888 inches Overall Width: 1.376 inches Cable Opening Diameter: 0.750 inches Cable Opening Diameter: 0.750 inches Cable Opening Diameter: 0.750 inches Sall Type: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded Dupling Thready Day Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Auminum alloy Surface Treatment: Cadmium Thread Size: Stright type wickale damp Surface Treatment: Cadmium Thread Solital Cadmiu Thread Solital Cadmiu<	Right-hand	
Overall Length:3.875 inchesOverall Height:1.888 inchesOverall Vidth:1.375 inchesCable Opening Diameter:0.750 inchesCable Opening Quantity:11Seal Type:Preformed packingMonting Facility Type And Quantity:1 threaded coupingThready type Inch (tp):28Preformed packingMonting Facility Type And Quantity:1 threaded coupingThready type Inch (tp):28SinchesCaluinu1/12 inchesSurface Treatment:CaluinuStyle Designator:CaluinuStright type wickable clampCaluinuThread Style Designator:CaluinuChrister Designator:CaluinuThread Type CaluinuCaluinuChrister Designator:CaluinuCaluinuThread Style Designator:CaluinuCa	Seal Material:	
3.85 inches Overall Height: 1.88 inches Overall Width: 1.375 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Participa Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thread Y Per Inch (tpi): 28 Thread Size: 1.125 inches Matrial: Aurinum alloy Surface Treatment: Cadnium Style Designator: Stradight type wicable clamp Stradight type wica	Rubber, neoprene latex	
Overall Height: 1.888 inches Overall Widht: 1.375 inches Cable Opening Diameter: 0.700 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Sea: 1.125 inches Matrial: Aturinum alloy Surface Treatment: Cadnium Style Designator: Stradight type wicable clamp Matrial: Aturinum alloy Style Designator: Stradight type wicable clamp Stradig	Overall Length:	
1.888 inches Overall Width: 1.375 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpl): 28 Thread Size: 1.125 inches Matrial: Aluminum alloy Surface Treatment: Cadmium Thread Series Designator: Unef Thread Series Designator: Unef Surface Treatment: Cadmium Thread Series Designator: Unef Surface Treatment: Surface Treatment:	3.875 inches	
Normal With: 1.375 Inches Cable Opening Diameter: 0.750 Inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpl): 28 Type: 1 threaded coupling Thready Qty Per Inch (tpl): 28 Type: 1 threaded coupling Thread Size: 1 thread Inchestop Aurnium alloy Surface Treatment: Cadmium Style Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Inter Gameter Cadmium Thread Series Designator: Inter Gameter </td <td>Overall Height:</td> <td></td>	Overall Height:	
1.375 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Strafes Designator: Cadmium Thread Series Designator: Unef Surface Treatment: Cadmium Thread Series Designator: Dref Measure: Cadmium Thread Series Designator: Inford Series Designator: Dref Infe: Na Dref Infer: Na Dret Infer: Na	1.888 inches	
Cable Opening Quantiy: 0.750 inches Cable Opening Quantiy: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Gype Indo (tpt)): 28 Preformed packing Munting Facility Type And Quantity: 1 threaded coupling Thready Gype Indo (tpt)): 28 Parecady Gype Type Indo (tpt)): 29 Stread Size: 1.125 inches Material: Alumium alloy Strafer Treatment: Cadmium Strafer Type w/cable clamp Strafer Type w/cable clamp Strafer Type w/cable clamp Cadmium Thread Series Designator: Cadmium Strafer Type w/cable clamp Strafer Type w/cable clamp Cadmium Thread Series Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator:	Overall Width:	
0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Pen Inch (tpi): 28 Pisteriation 1.125 inches Material: 1.125 inches Material: Auminum alloy Surface Treatment: Cadmium Stright Type webshe damp Stright Type webshe damp Cadmium Thread Series Designator: Unef Na Dried Measure: Interd Measure: <	1.375 inches	
Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Threads Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Cadmium Strigght type w/cable clamp Surface Treatment: Cadmium Strigght type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Unit of Measure: Vind Dind fue Surface Treatment: Cadmium Thread Series Designator: Unit of Measure: Vind Of Measure: Incol Int of Measure: Int of Measure: Into: No Stright type uit of the sure of the	Cable Opening Diameter:	
1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Cadmium Striggin type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Num Num Und full Cadmium Thread Series Designator: Num Und full Dief Life: Na Dief Jeise: Na Dief Measure: Image: Fine: Na Striggin Life: Interforme: Interforme: Interforme: Interforme: Interforme: Interforme: Interforme: Interforme: Interforme: Interforme: <tr td=""></tr>	0.750 inches	
Seal Type:Preformed packingMounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.125 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStright type w/cable clampStright type w/cable clampCadmiumThread Series Designator:CadmiumThread Series Designator:CadmiumThread Series Designator:Cutof Measure:NaPaint Information:NaFacility:NaFacility:NaFacility:NaFacility:NaFacility:NaFacility:NaFacility:NaFacility:NaFacility:NaFacility:NaFacility:NaFacility:Facility:NaFacility:Facility:NaFacility: <td< td=""><td>Cable Opening Quantity:</td><td></td></td<>	Cable Opening Quantity:	
Peformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 27 Thread Size: 1.125 inches Material: 1.125 inches Mat	1	
Nounting Facility Type And Quantity: 1 threaded coupling Thready Cay Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Straight type w/cable clamp Straight type w/cable clamp Cadmium Inferd Series Designator: Cadmium Thread Series Designator: Unef Shelf Life: Na Dun f Field Complement: Na Dun f Straight type w/cable clamp Straight type w/cable clamp Cadmium Thread Series Designator: Unef Shelf Life: Na Dut Of Measure: To Thread Series Designator: To Straight type w/cable clamp Straight type w/cable clamp Straight type w/cable cla	Seal Type:	
1 threaded coupling Thready Quy Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straface Treatment: Cadmium Style Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Unof Suff Life: Na Did f Measure: mainter Tread Series Designator: Suff Life: Na Did f Measure: Tread Series Designator: Suff Life: Na Did f Measure: Suff Life: Na Suff Life: Suff Life: Suff Life: Suff Life: Suff L	Preformed packing	
Thready Quy Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Unif Shelf Life: Na Unif Of Measure: - Denilitarization: No Fig:	Mounting Facility Type And Quantity:	
28 Thread Size: 1.125 inches Material: Autonium alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Straight type w/cable clamp Straface Treatment: Cadmium Thread Series Designator: Cadmium Shelf Life: Na Dinfor Measure: Denilitarization: No Fig:	1 threaded coupling	
Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Cadmium Strface Treatment: Strface Treatment: Cadmium Strface Treatment: Cadmium Strface Treatment: Cadmium Strface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: Na Dint Of Measure: Penilitarization: No Fig:	Thready Qty Per Inch (tpi):	
1.125 inches Material: Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Straight type w/cable clamp Cadmium Thread Series Designator: Unef Shelf Life: N/a Unef Shelf Life: N/a Lit Of Measure: Demilitarization: No Fig:	28	
Material:Aluminum alloySurface Treatment:CadmiumCadmiumStyle Designator:Straight type w/cable clampSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Thread Size:	
Aluminum alloy Surface Treatment: Cadmium Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unt of Measure: Demilitarization: No Fig:	1.125 inches	
Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unef Deli Desure: Fig:	Material:	
Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unt of Measure: Femilitarization: No Fig:	Aluminum alloy	
Style Designator:Straight type w/cable clampSurface Treatment:CadmiumCadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Surface Treatment:	
Straight type w/cable clampSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Cadmium	
Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:	
Cadmium Thread Series Designator: Unef Unef Shelf Life: N/a Unit Of Measure: Pomilitarization: No	Straight type w/cable clamp	
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:	
Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cadmium	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Fig:	Unef	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A10100	Fiig:	
	A10100	