

View Online at <https://aerobasegroup.com/nsn/5935-01-264-2828>

**Electrical Insulation Feature:**

Insulated completely

**Identification Code Color:**

Natural

**Body Style:**

Rivet mounted

**Mounting Bushing Length:**

Between 0.100 inches and 0.120 inches

**Body Length:**

0.530 inches

**Overall Diameter:**

0.235 inches

**Bushing Accommodation Hole Shape:**

Round

**Accommodated Finger Type:**

Test prod single finger

**Finger Accommodation Diameter:**

0.080 inches single finger

**Finger Accommodation Length:**

0.500 inches single finger

**Mounting Bushing Diameter:**

0.134 inches

**Bushing Thru-hole Accommodation Diameter:**

0.187 inches

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

1 bushing

**Terminal Type:**

Pin

**Material:**

Plastic, polytetrafluoroethylene body

**Material:**

Plastic polytetrafluoroethylene insulator

**Precious Material And Location:**

Spring contact and terminal surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Surface Treatment:**

Nickel bushing

**Surface Treatment:**

Nickel bushing

**Test Data Document:**

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-39024/15 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03400