

View Online at <https://aerobasegroup.com/nsn/5935-01-264-3241>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape threaded

Overall Length:

0.933 inches

Overall Diameter:

0.930 inches

Environmental Protection:

Corrosion resistant and vibration resistant and shock resistant and thermal shock resistant

Distance From Mounting Shoulder To Front Face:

0.698 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

2 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

End Application:

5895-01-195-0827 receiver-transmitter

Thread Length:

0.305 inches

Thread Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Stainless steel single mating end single contact grouping or copper alloy single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass fiber single mating end and plastic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Insert Material Specification:

Mil-m-14f, ty sgd military specification all material responses single mating end

Included Contact Quantity:

2 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.