

View Online at <https://aerobasegroup.com/nsn/5935-01-264-4370>

Thread Class:

2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

31.5 millimeters

Overall Height:

33.3 millimeters

Overall Width:

33.3 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 24.61 millimeters and 26.97 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 24.61 millimeters and 26.97 millimeters

Distance From Mounting Shoulder To Front Face:

20.9 millimeters

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16-35 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

80.0 and 180.0 and 215.0 and 298.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

10

Thread Size:

25.0 millimeters and 1.188 inches

Thread Pitch In Millimeters:

1.00

Insert Material:

Plastic epoxy single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Special Features:

Mounting slot width 3.25 millimeters

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-dod-c-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0