NSN 5935-01-264-5113

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-264-5113 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 2.969 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches **Environmental Protection:** Moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.147 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 24-9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.438 inches **Terminal Location:**

Torrinia Location.

Back single mating end single contact grouping

NSN 5935-01-264-5113

Mil-c-5015 spec.

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):