

View Online at <https://aerobasegroup.com/nsn/5935-01-264-8902>

**Thread Class:**

2b and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Right angle type

**Overall Length:**

1.485 inches

**Overall Height:**

0.706 inches

**Overall Width:**

0.360 inches

**Environmental Protection:**

Thermal shock resistant and vibration resistant and moisture resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

0.096 inches

**Distance Between Mounting Facility Centers:**

1.265 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

37 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Post jacksocket

**Thready Qty Per Inch (tpi):**

56 and 56 and 56

**Thread Size:**

0.086 inches and 0.086 inches and 0.086 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Shell Material:**

Metal

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074 military specification single treatment response

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification 1st material response single mating end and mil-m-14, type sdg-f military specification 2nd material response single mating end or mil-m-24519 military specification 3rd material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

37 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Jackscrew type-female and location-right hand and jackscrew type-female and location-left hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.037 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.