

View Online at <https://aerobasegroup.com/nsn/5935-01-264-8906>

Thread Class:

2b and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Right angle type

Overall Length:

0.785 inches

Overall Height:

0.608 inches

Overall Width:

0.407 inches

Environmental Protection:

Thermal shock resistant and vibration resistant and moisture resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

0.096 inches

Distance Between Mounting Facility Centers:

0.565 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

9 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Post jacksocket

Thready Qty Per Inch (tpi):

56 and 56 and 56

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Aluminum alloy 380.0

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Qq-n-290 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdg-f military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-female and location-right hand and jackscrew type-female and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.