

View Online at <https://aerobasegroup.com/nsn/5935-01-265-1948>

Body Style:

Hood, top opening w/clamp

Overall Length:

2.000 inches

Overall Height:

1.460 inches

Overall Width:

0.394 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof and thermal shock resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 2nd contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 2nd contact grouping

Shell Type:

Hood, top opening

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end 2nd contact grouping

Contact Material:

Copper alloy single mating end 2nd contact grouping

Contact Surface Treatment:

Gold single mating end 2nd contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end 2nd contact grouping

Terminal Type:

Tab, solder lug single mating end 2nd contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Type:

Round socket single mating end 2nd contact grouping

Special Features:

All parts to connector supplied unassembled

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.