

View Online at <https://aerobasegroup.com/nsn/5935-01-265-2987>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

33.8 millimeters

**Overall Height:**

38.0 millimeters

**Overall Width:**

38.0 millimeters

**Environmental Protection:**

Fuel resistant and shock resistant and vibration resistant and waterproof

**Unthreaded Mounting Hole Diameter:**

3.2 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

29.4 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

29.4 millimeters

**Distance From Mounting Shoulder To Front Face:**

19.0 millimeters

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-27 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

22.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end 1st contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end 1st contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.125 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and silver single mating end all contact groupings and rhodium single mating end all contact groupings

**Insert Material:**

Plastic polypropylene single mating end

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416c, cl 2, type 2 federal specification all treatment responses

**Included Contact Quantity:**

8 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver and contact surfaces rhodium

**Precious Material:**

Gold and silver and rhodium

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0