

View Online at <https://aerobasegroup.com/nsn/5935-01-265-4204>

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Gray

Body Style:

Rivet mounted

Mounting Bushing Length:

Between 0.160 inches and 0.180 inches

Body Length:

0.530 inches

Overall Diameter:

0.235 inches

Bushing Accommodation Hole Shape:

Round

Accommodated Finger Type:

Test prod single finger

Finger Accommodation Diameter:

0.080 inches single finger

Finger Accommodation Length:

0.500 inches single finger

Mounting Bushing Diameter:

0.134 inches

Bushing Thru-hole Accommodation Diameter:

0.187 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

1 bushing

Terminal Type:

Solder well

Material:

Plastic, polytetrafluoroethylene body

Material:

Plastic polytetrafluoroethylene insulator

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material And Weight:

0.001 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Nickel bushing

Surface Treatment:

Nickel bushing

Test Data Document:

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-39024/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03400