NSN 5935-01-265-8103

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-265-8103

| Thread Direction: |
|--|
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 41.06 millimeters |
| Overall Diameter: |
| 31.0 millimeters |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 13-4 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 20.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Detent |
| Thread Size: |
| 18.0 millimeters |
| Thread Pitch In Millimeters: |
| 1.00 |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Criticality Code Justification: |
| Feat |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |

NSN 5935-01-265-8103Electrical Plug Connector - Page 2 of 2



| Shell Surface Treatment: |
|--|
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416 federal specification single treatment response |
| Thread Tolerance Class: |
| 6g external |
| ncluded Contact Quantity: |
| 4 single mating end single contact grouping |
| ncluded Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Emi grounding |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.020 gold grains, troy |
| Precious Material: |
| Gold |
| Test Data Document: |
| 31349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| so m |
| Specification Data: |
| 31349-dod-c-38999/46 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| 4039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |
| |
| |