# NSN 5935-01-266-1574

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-266-1574

Body Style:
Right angle type
Overall Length:
6.150 inches
Overall Width:
0.385 inches
Body Height:
0.550 inches
Environmental Protection:
Heat resistant and cold resistant and vibration resistant and shock resistant and pressure proof and moisture resistant and salt water
resistant
Unthreaded Mounting Hole Diameter:
Between 0.640 inches and 0.670 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
21 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
90.0 and 0.0
End Application:
Alq-17 (v) 1
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Metal single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 type ii class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-613 comp 2 federal specification single material response single mating end single contact grouping

Anodize

**Shell Material:** 

Aluminum alloy 6061

**Shell Surface Treatment:** 

# NSN 5935-01-266-1574

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Mil-a-8625 type ii, class 2, dyed black military specification single treatment response

### **Shell Material Specification:**

Qq-a-200/8 federal specification single material response

### **Included Contact Quantity:**

168 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Item is made from p/n 2138273g032 w/pn 564-0023-00 keying pins

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

### Demilitarization:

Yes - demil/mli

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.