NSN 5935-01-266-5758

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-266-5758

Body Style:

Straight shape

Overall Length:

1.215 inches

Overall Height:

Between 3.095 inches and 3.125 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.118 inches and 0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

Between 0.764 inches and 0.768 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

67 all mating ends

Contact Removability:

Removable all mating ends all contact groupings

Polarization Method:

3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends and glass fiber all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

Criticality Code Justification:

Feat

NSN 5935-01-266-5758

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp all mating ends all contact groupings
Guide Design And Location:
Hexagon shape male post right-hand at 6 oclock
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal
specification single material response
Insert Material Specification:
Mil-m-14, ty gdi-30f, sdg-f military specification 1st material response all mating ends and mil-m-14, ty gdi-30f, sdg-f military specification 2nd
material response all mating ends or 1288 bx mfr ref 3rd material response all mating ends or mil-m-14 military specification 4th material
response all mating ends
Included Contact Type:
Round pin all mating ends all contact groupings
Special Features:
Nuclear hardness critical item
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.158 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.