NSN 5935-01-266-6090

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-266-6090

Body Style: Straight shape, external coupling w/backshell **Overall Length:** 3.679 inches **Overall Height:** 2.188 inches **Overall Width:** 2.188 inches **Environmental Protection:** Fungus resistant and heat resistant and cold resistant and vibration resistant and thermal shock resistant and salt water resistant and humidity resistant **Unthreaded Mounting Hole Diameter:** 0.198 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.688 inches **Distance From Mounting Shoulder To Front Face:** 2.504 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-14 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 110.0 and 250.0 Shell Type:

Connector Locking Method:

Detent

Solid

Operating Tempurature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-266-6090

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, ty ii, cl 2 federal specification all treatment responses
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
2-37 insert configuration
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Specification Data:
81205-280-36507 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.