NSN 5935-01-266-7610

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-266-7610	
Thread Class:	
2a and 2b and 2a	
Thread Direction:	
Right-hand and right-hand and right-hand	
Body Style:	
Straight shape	
Overall Length:	
1.680 inches	
Overall Height:	
0.531 inches	
Overall Width:	
0.750 inches	
Environmental Protection:	
Heat resistant and cold resistant	
Distance Between Mounting Facility Centers:	
1.375 inches	
Threaded Device Type:	
Coupling facility and mounting stud	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
75 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
3.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
450.0 single mating end single contact grouping	
Polarization Method:	
Jackscrew	
Connector Locking Method:	
Jackscrew-socket	
Thready Qty Per Inch (tpi):	
32 and 32 and 32	

Thread Size:

0.138 inches and 0.138 inches and 0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-266-7610

Electrical Receptacle Connector - Page 2 of 2



I	r	١	S	ρ	r	ŧ	ı	V	la	ıt	ρ	r	i	а	ı	•
ı		ı	J	c		L	ı	ш	C	ľ	c		ı	а	ı	

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, ty gdi-30 or gdi-30f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

75 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right handandjackscrew type-female and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.075 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.