

View Online at <https://aerobasegroup.com/nsn/5935-01-266-9946>

Body Style:

Straight edge type w/mounting flange

Overall Length:

144.37 millimeters

Overall Height:

23.0 millimeters

Overall Width:

8.90 millimeters

Distance Between Mounting Facility Centers:

137.16 millimeters

Board Accommodated Length:

125.73 millimeters single board

Board Accommodated Width:

Between 1.42 millimeters and 1.83 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

450.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

64 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.064 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.