

View Online at <https://aerobasegroup.com/nsn/5935-01-267-1055>

Overall Length:

4.015 inches

Overall Width:

Between 2.109 inches and 2.140 inches

Environmental Protection:

Corrosion resistant and vibration resistant and shock resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

"3, 5-15" all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

15.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 all mating ends all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Friction

End Application:

4933-01-216-9309 test set, electronic system

Terminal Location:

Side all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Nickel all mating ends all contact groupings

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Qq-n-290 federal specification single treatment response all mating ends all contact groupings

Terminal Type:

Screw all mating ends all contact groupings

Contact Material Specification:

Astm b31, b49, b133 or b187 assn standard single material response all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Material Specification:

Astm b26, b209 or b221 assn standard single material response

Insert Material Specification:

Mil-m-14, type mai-30 or type mmi-30 military specification single material response all mating ends

Special Features:

Knockouts on side

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.