## NSN 5935-01-267-1055

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-267-1055

Overall Length:

4.015 inches

**Overall Width:** 

Between 2.109 inches and 2.140 inches

**Environmental Protection:** 

Corrosion resistant and vibration resistant and shock resistant

**Mating End Quantity:** 

2

**Contact Position Arrangement Style:** 

"3, 5-15" all mating ends

**Contact Removability:** 

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:** 

15.0 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:** 

125.0 all mating ends all contact groupings

**Polarization Method:** 

Contact

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**End Application:** 

4933-01-216-9309 test set, electronic system

**Terminal Location:** 

Side all mating ends all contact groupings

**Contact Material:** 

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:** 

Nickel all mating ends all contact groupings

**Insert Material:** 

Plastic all mating ends

**Contact Surface Treatment Specification:** 

Qq-n-290 federal specification single treatment response all mating ends all contact groupings

**Terminal Type:** 

Screw all mating ends all contact groupings

**Contact Material Specification:** 

Astm b31, b49, b133 or b187 assn standard single material response all mating ends all contact groupings

**Shell Material:** 

Aluminum alloy

**Shell Material Specification:** 

Astm b26, b209 or b221 assn standard single material response

## NSN 5935-01-267-1055

Electrical Receptacle Connector - Page 2 of 2



Insert	Material	Specific	ation:
ແນວເຂ	water iai	Specific	auvii.

Mil-m-14, type mai-30 or type mmi-30 military specification single material response all mating ends

**Special Features:** 

Knockouts on side

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.