

View Online at <https://aerobasegroup.com/nsn/5935-01-267-3125>

Body Style:

Right angle type

Overall Length:

6.150 inches

Overall Width:

0.385 inches

Body Height:

0.550 inches

Environmental Protection:

Heat resistant and cold resistant and vibration resistant and shock resistant and pressure proof and moisture resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

Between 0.640 inches and 0.670 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

21 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

180.0 and 270.0

End Application:

Alq-17 (v) 1

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Metal single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type ii class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613 comp 2 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 type ii, class 2, dyed black military specification single treatment response

Shell Material Specification:

Qq-a-200/8 federal specification single material response

Included Contact Quantity:

168 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Item is made from p/n 2138273g032 w/pn 564-0023-00 keying pins

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.