## NSN 5935-01-267-3970

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-267-3970

Body Style:
Right angle type
Overall Length:
2.800 inches
Overall Height:
0.490 inches
Overall Width:
0.350 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.550 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end 1st contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Side single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end 1st contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Pin single mating end 1st contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end 1st contact grouping

**Guide Design And Location:** 

D shape pin left-hand at 12 oclock and d shape socket right-hand at 12 oclock

## NSN 5935-01-267-3970

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

**Included Contact Quantity:** 

46 single mating end 1st contact grouping

**Included Contact Type:** 

Round pin single mating end 1st contact grouping

**Special Features:** 

Coaxial contact omitted

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.047 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.