Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-267-6615

## Body Style:

Straight shape, external coupling w/backshell

## **Overall Length:**

3.679 inches

# **Overall Height:**

2.188 inches

**Overall Width:** 

2.188 inches

## **Environmental Protection:**

Fungus resistant and heat resistant and cold resistant and vibration resistant and thermal shock resistant and salt water resistant and humidity resistant

Unthreaded Mounting Hole Diameter:

0.198 inches

# Center To Center Distance Between Mounting Facilities Parallel To Height:

1.688 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.688 inches

## Distance From Mounting Shoulder To Front Face:

2.504 inches

### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

16-14 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

80.0 and 280.0

#### Shell Type:

Solid

# **Connector Locking Method:**

Detent

## **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping



# **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, ty ii, cl 2 federal specification all treatment responses **Included Contact Quantity:** 37 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** 2-37 insert configuration **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.037 gold grains, troy **Precious Material:** Gold **Specification Data:** 81205-280-36507 manufacturers source control Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.