## NSN 5935-01-267-6616

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-267-6616 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.925 inches **Overall Height:** 0.659 inches **Overall Width:** 0.298 inches **Environmental Protection:** Vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** Between 0.088 inches and 0.094 inches **Distance Between Mounting Facility Centers:** 0.715 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Jackscrew

Thready Qty Per Inch (tpi):

56

**Thread Size:** 

0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-267-6616

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic polyester single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, grade c, cl 1 military specification single treatment response single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response or qq-a-200/8 federal specification single material response
Insert Material Specification:
Mil-m-24519, type gpt-30f military specification single material response single mating end
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Twisted pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-g-45204 spec.

Mil-std (military Standard):