## NSN 5935-01-267-7139

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-267-7139

Body Style:
Straight type
Overall Length:
3.500 inches
Overall Height:
0.637 inches
Overall Width:
0.350 inches
Environmental Protection:
Corrosion resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.250 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single
material response single mating end single contact grouping

**Unable To Decode:** 

**Insert Material Specification:** 

Unable to decode and unable to decode

Mil-p-46174, cl 40, grade military specification single material response single mating end

## NSN 5935-01-267-7139

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
80 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.080 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.