NSN 5935-01-268-1854

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-268-1854
Thread Class:
2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.520 inches
Overall Height:
1.220 inches
Overall Width:
1.220 inches
Unable To Decode:
Unable to decode and unable to decode
Unable To Decode:
Unable to decode and unable to decode
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.906 inches and 0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.906 inches and 0.969 inches
Distance From Mounting Shoulder To Front Face:
0.823 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Afdy 15-5 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
113.0 and 156.0 and 182.0 and 292.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
End Application:
4920-01-165-9220 interconnecting group
Thready Qty Per Inch (tpi):

10

NSN 5935-01-268-1854

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
22.0 millimeters and 1.000 inches
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Thread Tolerance Class:
6g external
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Iso m and special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.