# NSN 5935-01-268-2938

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-268-2938 **Thread Class:** 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.305 inches **Overall Diameter:** 1.890 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 25-61 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 49.0 and 169.0 and 200.0 and 244.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **End Application:** 4920-01-165-9220 interconnecting group Thready Qty Per Inch (tpi): 10

#### **Thread Size:**

37.0 millimeters and 1.675 inches

### **Thread Pitch In Millimeters:**

1.00

#### **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic epoxy single mating end

# NSN 5935-01-268-2938

Electrical Plug Connector - Page 2 of 2



| Contact Surface Treatment Specification:   |
|--|
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type:   |

Crimp single mating end single contact grouping

**Shell Material:** 

Stainless steel

**Shell Surface Treatment:** 

**Passivate** 

**Thread Tolerance Class:** 

6g external

**Included Contact Quantity:** 

61 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.061 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Iso m and special acme

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.