

View Online at <https://aerobasegroup.com/nsn/5935-01-268-2940>

Thread Class:

2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.305 inches

Overall Diameter:

1.279 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Afdy 15-5 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

113.0 and 156.0 and 182.0 and 292.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

End Application:

4920-01-165-9220 interconnecting group

Thready Qty Per Inch (tpi):

10

Thread Size:

22.0 millimeters and 1.000 inches

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Thread Tolerance Class:

6g external

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Iso m and special acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.