NSN 5935-01-268-4504

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-268-4504
Body Style:
Pcb, external coupling
Overall Length:
0.419 inches
Overall Height:
0.189 inches
Overall Width:
0.189 inches
Environmental Protection:
Corrosion resistant and moisture resistant and shock resistant and vibration resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.100 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.100 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Spring friction
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold and copper
Shell Surface Treatment Specification:
Qq-s-365 federal specification 1st treatment response

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-01-268-4504

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Ty	pe:
----------	---------	----	-----

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.