# NSN 5935-01-268-6459

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-268-6459 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.430 inches **Overall Height:** 1.031 inches **Overall Width:** 1.031 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 12-dec single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 18.0 and 138.0 and 208.0 and 268.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thread Length:

0.281 inches

Thready Qty Per Inch (tpi):

20 and 20

# NSN 5935-01-268-6459

Electrical Receptacle Connector - Page 2 of 3



Γh	rea	d	Si	ze:
	ıca	u	J	LC.

0.750 inches and 0.875 inches

#### **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic epoxy single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium

# **Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

# **Shell Material Specification:**

Qq-a-367 federal specification single material response

# **Included Contact Quantity:**

12 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.012 gold grains, troy

# **Precious Material:**

Gold

# **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unef and unef

# **Specification Data:**

81349-mil-c-83723/83 government specification

# Shelf Life:

N/a

## **Unit Of Measure:**

# Demilitarization:

# NSN 5935-01-268-6459

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.