

View Online at <https://aerobasegroup.com/nsn/5935-01-268-6462>

Body Style:

Right angle type

Overall Length:

2.190 inches

Overall Height:

0.563 inches

Overall Width:

0.363 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

0.062 inches

Distance Between Mounting Facility Centers:

2.050 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Contact

Connector Locking Method:

Friction

Terminal Location:

Side single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade d, cl 1 military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end 1st contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification all material responses single mating end

Included Contact Quantity:

35 single mating end 1st contact grouping

Included Contact Type:

Hermaphrodite single mating end 1st contact grouping

Special Features:

Polarizing pin located in contact position 2

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.035 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/53 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.