Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-269-0839

Body Style:

Straight shape

Overall Length:

0.996 inches

Overall Height:

0.585 inches

Overall Width:

0.124 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant

Unthreaded Mounting Hole Diameter:

Between 0.108 inches and 0.113 inches

Distance Between Mounting Facility Centers:

0.800 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

End Application:

1440-01-215-4868 armament subsystem

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end and glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single

material response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification: Mil-m-14g, type mhf military specification all material responses single mating end **Included Contact Quantity:** 5 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Mounting holes located on side of connector; cavity to accept polarizing pin located in position 5 **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.