## NSN 5935-01-269-0855



Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-269-0855

view offilite at https://aerobasegroup.com/hist//0300-01-203-0000
Thread Class:
2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.280 inches
Overall Diameter:
1.636 inches
Environmental Protection:
Thermal shock resistant and vibration resistant and shock resistant and pressure proof and heat resistant and humidity resistant and
corrosion resistant and hermetic
Distance From Mounting Shoulder To Front Face:
1.140 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
15-35 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
124.0 and 152.0 and 219.0 and 265.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
10
Thread Size:
1.000 inches and 28.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping

Contact Material:

Nickel single mating end single contact grouping and iron alloy 52 single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-269-0855

Electrical Receptacle Connector - Page 2 of 2



## Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Steel comp 316 or steel comp 321 or steel comp 347

**Shell Surface Treatment:** 

**Passivate** 

**Thread Tolerance Class:** 

6g external

**Included Contact Quantity:** 

37 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.037 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Special acme and iso m

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.