# NSN 5935-01-269-2634

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-269-2634 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.951 inches **Overall Height:** 1.125 inches **Overall Width:** 1.125 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.506 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 10000.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 105.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 20

**Thread Size:** 

0.812 inches

# NSN 5935-01-269-2634

Electrical Receptacle Connector - Page 2 of 3



arm	ına	 _ocation	•
	ша	 _UCALIUII	-

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Rubber synthetic single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Nickel

## **Shell Surface Treatment Specification:**

Mil-c-26074 military specification single treatment response

# **Shell Material Specification:**

Qq-a-225 federal specification single material response

# **Insert Material Specification:**

Zz-r-765 federal specification single material response single mating end

# **Included Contact Quantity:**

7 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.007 gold grains, troy

# **Precious Material:**

Gold

# **Thread Series Designator:**

Unef

# Shelf Life:

N/a

## **Unit Of Measure:**

--

# Demilitarization:

No

# Fiig:

A039b0

# NSN 5935-01-269-2634

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.