Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-269-5305

| Thread Class: |
|------------------------------------------------------------|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling, w/clamp |
| Environmental Protection: |
| Fuel resistant and heat resistant and cold resistant |
| Mounting Facility Thickness: |
| Between 0.080 inches and 0.375 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Connector Locking Method: |
| Bayonet latch |
| End Application: |
| 6680-00-050-9744 |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 1.125 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Metal single mating end single contact grouping |
| Terminal Type: |
| Crimp and solder single mating end single contact grouping |
| Shell Material: |
| Metal |
| Included Contact Quantity: |
| 8 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| · Furnished items - potting boot |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| |

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0