NSN 5935-01-269-5896

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-269-5896
Body Style:
Straight shape, external coupling
Overall Length:
0.697 inches
Overall Height:
1.703 inches
Overall Width:
1.703 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.147 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.688 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.688 inches
Distance From Mounting Shoulder To Front Face:
0.447 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
29 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-269-5896

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-c-38999 spec.

A039b0