

View Online at <https://aerobasegroup.com/nsn/5935-01-270-0108>

**Overall Length:**

0.310 inches

**Overall Height:**

0.862 inches

**Overall Width:**

0.196 inches

**Environmental Protection:**

Thermal shock resistant and humidity resistant and salt water resistant and vibration resistant and shock resistant

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

300.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-20693, type 1 military specification single material response single mating end

**Included Contact Quantity:**

2 single mating end single contact grouping

**Included Contact Type:**

Spring pincers single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.002 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.