Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-270-1792

Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
34.16 millimeters
Overall Diameter:
49.89 millimeters
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
110.0 and 250.0
Shell Type:
Solid
Connector Locking Method:
Detent
Thread Size:
37.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Og n 416 føderel angeifigetign gingle treatment response

Qq-p-416 federal specification single treatment response

NSN 5935-01-270-1792

Electrical Plug Connector - Page 2 of 2



**Thread Tolerance Class:** 

6g external

**Included Contact Quantity:** 

8 single mating end 1st contact grouping

## Included Contact Type:

Round pin single mating end all contact groupings

## **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.056 gold grains, troy

#### **Precious Material:**

Gold

### **Test Data Document:**

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

lso m

### Specification Data:

81349-dod-c-38999/49 government specification

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

# Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.