## NSN 5935-01-270-3544

**Contact Surface Treatment Specification:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-270-3544

Body Style:
Straight shape, external coupling strain relief
Overall Height:
1.688 inches
Overall Width:
1.688 inches
Body Length:
2.824 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.156 inches and 1.297 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.156 inches and 1.297 inches
Cable Entrance Diameter:
0.625 inches
Distance From Mounting Shoulder To Front Face:
Between 0.556 inches and 0.587 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
20-41 single mating end
Contact Removability:
Contact Removability:  Removable single mating end single contact grouping
Removable single mating end single contact grouping
Removable single mating end single contact grouping  Polarization Method:
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  45.0
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  45.0  Shell Type:
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  45.0  Shell Type:  Solid
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  45.0  Shell Type:  Solid  Connector Locking Method:
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  45.0  Shell Type:  Solid  Connector Locking Method:  Bayonet pin
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  45.0  Shell Type:  Solid  Connector Locking Method:  Bayonet pin  Connector Cable Strain Relief Method:
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  45.0  Shell Type:  Solid  Connector Locking Method:  Bayonet pin  Connector Cable Strain Relief Method:  Cable clamp
Removable single mating end single contact grouping  Polarization Method:  Keyway or multiple keyway  Insert Position In Deg:  45.0  Shell Type:  Solid  Connector Locking Method:  Bayonet pin  Connector Cable Strain Relief Method:  Cable clamp  Terminal Location:

Mil-g-45204, type 1, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290,

grade e federal specification 2nd treatment response single mating end single contact grouping

## NSN 5935-01-270-3544

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
41 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.041 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms3128 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.