## NSN 5935-01-270-9552

Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-270-9552

| Body Style:  |
|--|
| Straight shape, external coupling  |
| Overall Length:  |
| 1.039 inches   |
| Overall Height:  |
| 1.219 inches   |
| Overall Width:   |
| 1.219 inches   |
| Unthreaded Mounting Hole Diameter:   |
| Between 0.123 inches and 0.138 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Height:                              |
| 0.969 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:                            |
| 0.969 inches   |
| Distance From Mounting Shoulder To Front Face:   |
| Between 0.815 inches and 0.820 inches  |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| Afdy 15-5 single mating end  |
| Contact Removability:  |
| Removable single mating end single contact grouping  |
| Polarization Method:   |
| Keyway or multiple keyway  |
| Insert Position In Deg:  |
| 0.0  |
| Shell Type:  |
| Solid  |
| Connector Locking Method:  |
| Bayonet pin  |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Contact Surface Treatment Specification:   |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type:   |
| Crimp single mating end single contact grouping  |
| Shell Material:  |

## NSN 5935-01-270-9552

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment:   |
|--|
| Cadmium  |
| Shell Surface Treatment Specification:   |
| Qq-p-416 federal specification single treatment response   |
| Included Contact Quantity:   |
| 5 single mating end single contact grouping  |
| Included Contact Type:   |
| Round socket single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.025 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 96906-ms27505 government standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):   |
| Mil-g-45204 spec.  |