

View Online at <https://aerobasegroup.com/nsn/5935-01-270-9554>

Body Style:

Straight shape

Overall Length:

1.198 inches

Overall Height:

6.995 inches

Overall Width:

Between 1.790 inches and 1.810 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.148 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 6.340 inches and 6.360 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.421 inches and 1.431 inches

Distance From Mounting Shoulder To Front Face:

1.102 inches

Mating End Quantity:

3

Contact Removability:

Removable 2nd mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back 1st mating end 4th contact grouping

Contact Material:

Copper alloy 3rd mating end single contact grouping

Contact Surface Treatment:

Gold 2nd mating end single contact grouping

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response 1st mating end 4th contact grouping

Terminal Type:

Crimp 3rd mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response 3rd mating end single contact grouping

Shell Material:

Aluminum alloy 380.0

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response

Special Features:

Polarizing posts or keys not installed but supplied with connector

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.355 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.