NSN 5935-01-270-9997

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-270-9997

Body Style:
Straight shape, external coupling w/backshell
Overall Height:
1.141 inches
Overall Width:
1.141 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.453 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.453 inches
Distance From Mounting Shoulder To Front Face:
0.447 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
14-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
66.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:

37 single mating end single contact grouping

NSN 5935-01-270-9997

Electrical Receptacle Connector - Page 2 of 2



ncluded	Contact	Type:
---------	---------	-------

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

She	elf	Lif	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.