NSN 5935-01-271-1732

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-271-1732

Body Style: Straight edge type w/card guide **Overall Length: 3.739** inches Overall Width: 0.340 inches **Body Height:** 0.458 inches **Environmental Protection:** Shock resistant and vibration resistant and humidity resistant **Board Accommodated Length:** 3.596 inches single board **Board Accommodated Width:** Between 0.054 inches and 0.071 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:**

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass single mating end and plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-q-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

NSN 5935-01-271-1732

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.