# NSN 5935-01-271-4777

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-271-4777

Body Style:
Straight shape
Overall Length:
7.150 inches
Overall Height:
0.960 inches
Overall Width:
0.250 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
6.900 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Wire wrap single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-530 federal specification single material response single mating end single contact grouping

## NSN 5935-01-271-4777

Electrical Receptacle Connector - Page 2 of 2



### **Guide Design And Location:**

D shape pin right-hand at 12 oclock and d shape socket left-hand at 12 oclock

### **Insert Material Specification:**

Mil-m-14f, type sdgf military specification 1st material response single mating end and mil-m-14f, type sdgf military specification 2nd material response single mating end or mil-p-46174 military specification 3rd material response single mating end

### **Included Contact Quantity:**

120 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:** 

No locktite on hardware

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.120 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.