

View Online at <https://aerobasegroup.com/nsn/5935-01-271-5697>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Rectangular shape

Overall Length:

2.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.282 inches

Overall Height:

0.942 inches

Overall Width:

1.234 inches

Unthreaded Mounting Hole Diameter:

0.136 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.765 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

90 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

8.5 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Post jacksocket

Thready Qty Per Inch (tpi):

24

Thread Size:

0.190 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Guide Design And Location:

Key shape socket right-hand at 6 oclock key shape socket left-hand at 12 oclock

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

90 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.090 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.