

View Online at <https://aerobasegroup.com/nsn/5935-01-272-4350>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.850 inches

Overall Diameter:

0.312 inches

Environmental Protection:

Heat resistant and cold resistant

Cable Entrance Diameter:

0.160 inches

Distance From Mounting Shoulder To Front Face:

0.450 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

36 and 36

Thread Size:

0.250 inches and 0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, class 4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Gold and nickel

Shell Surface Treatment Specification:

Mil-g-45204, type 1, gr c, cl 1 military specification 1st treatment response and qq-n-290 federal specification 2nd treatment response

Shell Material Specification:

Astm a 582, cl 303, cond a assn standard single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.