

View Online at <https://aerobasegroup.com/nsn/5935-01-272-6247>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

6.660 inches

**Overall Diameter:**

1.630 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

**Cable Entrance Diameter:**

Between 0.562 inches and 0.937 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-21 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

344.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, class c federal specification all treatment responses

**Included Contact Quantity:**

21 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.021 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.