Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-272-9498

Body Style:

Right angle type

Overall Length:

Between 5.290 inches and 5.310 inches

Overall Width:

Between 0.735 inches and 0.775 inches

Body Height:

Between 0.395 inches and 0.400 inches

Environmental Protection:

Heat resistant and cold resistant and humidity resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.128 inches and 0.132 inches

Distance Between Mounting Facility Centers:

Between 5.025 inches and 5.035 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1200.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, gr c military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping



Contact Material Specification: Qq-b-626 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty sdg-f military specification all material responses single mating end **Included Contact Quantity:** 47 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Polarizing pins located at positions b and f **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.047 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.