NSN 5935-01-273-2170

Included Contact Type:

Round socket single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-273-2170

Body Style: Rectangular shape **Overall Length:** 2.760 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.390 inches **Overall Height:** 0.625 inches **Overall Width:** 1.536 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.150 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.878 inches **Mating End Quantity: Contact Position Arrangement Style:** 25-104 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material responses single mating end **Included Contact Quantity:** 104 single mating end single contact grouping

NSN 5935-01-273-2170

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.104 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-28748/6 government specification
Shelf Life:
N/a
Unit Of Measure:
- -
Demilitarization:
No
Fiig:
A039b0