

View Online at <https://aerobasegroup.com/nsn/5935-01-273-2525>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.468 inches

Bushing Diameter:

Between 0.378 inches and 0.381 inches

Overall Height:

Between 0.680 inches and 0.700 inches

Overall Width:

Between 0.680 inches and 0.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.496 inches and 0.504 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.496 inches and 0.504 inches

Distance From Mounting Shoulder To Front Face:

Between 0.540 inches and 0.570 inches

Threaded Device Type:

Coupling facility and mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz single mating end single contact grouping

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Size:

0.438 inches and 0.099 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0