NSN 5935-01-273-3465

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-273-3465

view Online at https://aerobasegroup.com/nsn/0000-01-270-0400
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.938 inches
Overall Diameter:
1.513 inches
Environmental Protection:
Moisture resistant and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
19-42 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
62.0 and 145.0 and 180.0 and 280.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
End Application:
Computer set, an/uyk-43
Thready Qty Per Inch (tpi):
18 and 10
Thread Size:
1.125 inches and 1.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

Insert Material:

Plastic fluorosilicone single mating end

NSN 5935-01-273-3465

Electrical Plug Connector - Page 2 of 2



4		ation single treatme				
\/iii_a_//よン()// r	military endeities	ation cinala traatm <i>i</i>	ant rachanca c	naitem albair	and cinala	contact arouning
VIII-U-4JZU4 I	IIIIIIlai v Succiiica	ilion sinuic licalini		niiui c ilialiiu	CITA SILIAIC	contact dioublild

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate and nickel

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response

Included Contact Quantity:

42 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.042 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and double stub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.